



Angle of impact		45°	90°	180°
Tested impact energy (Joules)		800	1000	800
Equivalent vehicle weight (kg)		2000	2000	2000
Equivalent vehicle speed (kmph)		3.2	3.6	3.2
Material Properties				
Temperature	MEMAPLEX™	-15°C to +50°C		
Temperature	MEMAPLEX®	-40°C to +30°C		
Chemical Resistance		Excellent - ISO / TR 10358		
Fire Rating		HB / F		
Food Contact		Yes		
Toxicity		None		
Conductivity		No		
Environment				
CO ₂ / m		3.57		
Recyclability		100%		

Terms and conditions apply.
Standard Warranty 2 years.

Optional Extras




Internal Rubber Grips




RackGuard Tool Set




Part No.	Description	A - Rack width (max)	B - Rack depth (max)
P-03-01-0017	iFlex RackGuard (S) SL - 600mm	102	45
P-03-01-0021	iFlex RackGuard (S) ML - 600mm	102	68
P-03-01-0025	iFlex RackGuard (S) LL - 600mm	102	80
P-03-01-0018	iFlex RackGuard (S) SLR - 600mm	85	45
P-03-01-0022	iFlex RackGuard (S) MLR - 600mm	85	68
P-03-01-0026	iFlex RackGuard (S) LLR - 600mm	85	80
P-03-01-0029	iFlex RackGuard (L) SL - 600mm	126	75
P-03-01-0030	iFlex RackGuard (L) SLR - 600mm	112	75
S-01-02-0011	RackGuard Tool Set		




P-03-01-0017
P-03-01-0021
P-03-01-0025



P-03-01-0018
P-03-01-0022
P-03-01-0026



P-03-01-0029



P-03-01-0030

* iFlex RackGuards are also available in 400mm, 1000mm and bespoke sizes, as well as with internal rubber lugs. All iFlex RackGuards are available in the Memaplex FR option.